4-Post-Lift

Item No.: TW445









Description

Electro-hydraulic four-post lift.

With rear squirm plates and front recesses for optional turntables. This lift is ideal for wheel alignment and all other service work. Jacking beam also optionally available.

Features

- 1A Quality built with CE-Certificate
- Manufactured in accordance to ISO 9001
- Lift capacity 4500 kg
- CE-Certificate
- IP 54 24V control box
- 24 V limit switch
- Hydraulic overflow valve
- Roll off protection
- · Safety lock for entire lifting height
- · Cable break safety device
- · Sliding plates
- Foot protection
- · Acoustic warning signal

- Delivery contents

- Lift incl. Power unit
- Heavy duty anchor bolts (16 pcs.)
- Examination book and CE-Certificate
- Optional: Turntables (TW445-D)
- Optional: Jacking beam (2 t / Pneumatic) (TW445-W)
- Optional: Drive on ramp (TW445-R)
- Optional: Runway extensions front (TW445-V) and rear (TW445-H)
- Assembly video online | Product video online










Product Assembly


















Dimensions


Minimal wheel base for the alignment: 1600 mm

Maximum wheel base for the alignment: 3700 mm | Maximum wheel base for the lift: 4320 mm

Total length of the lift (including ramps): 5867 mm

Foundation requirement: (L) 5140 mm x (W) 3400 mm x (concrete strength C20/25) 150 mm





Further information to be found at www.twinbusch.de

Technical Data

Lifting capacity	4500 kg
Lifting height max.	1850 mm
Runway length	4510 mm
Runway width	536 mm
Drive on height	126 mm
Lifting time (approx.)	50 sec.
Power supply	400 V / 3 Phase
Motor power	2,2 kW
Fusing	16 A / type C
Weight (approx.)	1400 kg

Optional accessory



Turntables Item No.; TW445-D Turntables for wheel alignment



Jacking beam Item No.: TW445-W



Runway extensions (front) Item No.: TW445-V 2 piece in the set

Runway extensions (rear) Item No.: TW445-H 2 piece in the set Further accessories can be found at www.twinbusch.co.uk





2 piece in