Low rise scissor lift

Item No.: TWS3-10E /-G / TWS3-10E-FZ









Description

Low rise scissor lift.

1000 mm lifting height. Ideal for tyre service, painting and body work. With electromagnetic release. No compressed air supply is required. The platform can be lengthened by locking the drive on ramps. A very practical mobile kit is available as an option.

Features

- 1A Quality built with CE-Certificate
- Manufactured in accordance to ISO 9001
- Mechanical synchronization control of both lifting platforms for perfect synchronism
- Low drive over height (110 mm)
- FAILSAFE safety lock system (monitoring of the detent position)
- Double line system for symmetrical distribution of the system pressure
- High quality solid construction
- Emergency lowering function in case of power failure
- · Direct actuation by two powerful hydraulic cylinders
- Automatic safety lock
- Foot protection
- Acoustic warning signal (foot protection)
- · High quality powder coating

Delivery contents

- Lift incl. Power unit | Rubber blocks
- English instruction manual
- Examination book | CE-Certificate
- · Assembly video online
- · Product video online







Assembly

video 🔳

Transporter class

middle

Vehicle type / Wheelbase











short middle short




middle long



Dimensions





Further information to be found at www.twinbusch.co.uk

Technical Data -

Lifting capacity	3000 kg
Lifting height max.	1000 mm + Rubber
Drive on height	110 mm
Lifting, lowering time (approx.)	20/20 sec.
Power supply	400 V or 230 V
Motor power	2,2 kW
Fusing	16 A / type C
Weight (approx.)	500 kg
**Planca note: The TMCO 10F F7 is only	

**Please note: The TWS3-10E-FZ is only

Optional accessory





Drive on ramps Item No.: TWS3-10-R 4 pieces in the set

Perfect for sport cars



RAL 7016



RAL 5015 Galvanized TWS3-10-R TWS3-10-R-G TWS3-10-R-FZ

Further accessories can be found at www.twinbusch.co.uk